



RRM/EC Round grid magnets

Separation systems for various industries



Bakker Magnetics

Always ahead.

Datasheet Bakker Magnetics

RRM Round grid magnets

version 1.0

- Execution : Round grid magnet easy clean type RRM/EC
Sturdy construction
Permanent magnetic
Standard fitted with Jacob flange
- Housing : Stainless steel 1.4301
- Surface treatment : Blasted
- Magnetic part : Permanent Neodymium magnets
25.120/01 – 25.124/01: quality BM48H
25.126/01 – 25.128/01: quality BM40H

Standard ceramic version (RM) Square

Article number	A ∅	B	C	# Bars	Weight (kg)
25.120/01	100	50	80	2	1,5
25.121/01	150	50	120	3	3,0
25.122/01	200	50	120	4	4,0
25.123/01	250	50	120	5	5,5
25.124/01	300	50	120	6	7,0
25.126/01	400	55	2 x 120	8	9,0
25.128/01	500	55	2 x 120	10	11,5

Sizes and dimensions (in mm) as shown on the drawing on the last page.

For more information or questions please contact us:

Bakker Magnetics

Sciencepark Eindhoven 5502
5692 EL Son, The Netherlands

Division: Magnetic Separation Technology

Phone : +31 (0) 40 2 678 840

Mail : mst@bakkermagnetics.com

Dimensions and shape of the magnet, in combination with required manufacturing processes, may cause the magnetic and physical characteristics to vary from typical values. Therefore, all data presented in this document are for general reference only and should not be relied upon to represent standard characteristics, nor are they guaranteed upon use. Bakker Magnetics reserves the right to change information in this document, including magnet performance standards, specifications, and characteristics without notice.



Bakker Magnetics

Always ahead.

