

HS 水力栅/水力筛/静态筛



HS

关于产品：

水力栅是一种用于污水处理过程使用的固液分离装置。

应用领域：

工业废水预处理：造纸，纺织，制革，印染，化工以及屠宰行业。
水力栅提供了一种经济、可连续运行的固液分离系统解决方案，
无需维护与电耗。

As a pretreatment equipment in industrial waste water with a mesh of between 0.5 and 1 mm, to eliminate the thick waste in the paper, textile, tanning, laundry, canning and milk industries and abattoirs etc.
The static screen offers an economic solution in the continuous solid-liquid separation process with almost no maintenance requirements and no energy input at all.

特点及优势

- 废水预处理的最理想固液分离选择
- 全不锈钢材质，坚固耐用。
- 性价比高、无需维护、无电能消耗。

型号 Model	筛网间距/筛网 Mesh size & Capacity (m ³ /h)				规格尺寸/Dimension (mm)			
	0.2mm	0.5mm	1.0mm	1.5mm	2.0mm	L	W	H
HS-300	3	6	13	19	30	1420	430	1900
HS-500	5	10	22	32	50	1420	630	1900
HS-600	6	12	27	39	60	1420	700	1900
HS-800	8	16	36	52	80	1420	930	1900
HS-1000	10	20	45	65	100	1420	1130	1900
HS-1500	15	30	65	100	150	1420	1630	1900

